



Decorative Aerators

Our lake aerators are built of quality stainless and composite components. They have minimal depth requirements and may even be used in salt water!

High electrical efficiency and excellent oxygen transfer combine to provide beautiful performance at a practical price.

Model	Volt/Amp	Height	Diameter	Min Depth
1/2 hp	120V / 5A	3.5 ft	12 ft	15 in
3/4 hp	120V / 6.7A	4.5 ft	15.5 ft	18 in
3/4 hp	230V / 3.8A	4.5 ft	15.5 ft	18 in
2 hp	230V / 10A	see next page		20 in



1/2 and 3/4 hp spray pattern
(See chart for diameter)

Configuration and Controls



Systems have a one year warranty and include a UL listed GFCI protected outdoor control panel and timer. 230 Volt units include a 12 Volt transformer for the optional three 75 Watt light fixtures.

Cables are available in 25 foot increments to 200 ft. All units can be shipped by UPS. Motors are 60Hz. For special configurations please contact us.



1/2 and 3/4 hp float body

Lighting



Fan pattern (all models)



Brass High-Intensity
12V Underwater Fixture



Two Tier Pattern (2hp only)

The use of wet/dry listed fixtures allows the three fixtures to be mounted right at the waterline. This produces maximum brightness by eliminating absorption through a layer of water.

Two Horsepower Decorative Aerator

The two horsepower model includes five nozzle adapters. Changing the spray pattern is as easy as unthreading one nozzle and replacing it with another.

Interchangeable nozzles permit the spray pattern to be tailored to the size of the lake or to personal taste.

With miserly depth and electrical requirements for a unit of this capacity, this model provides versatile display capabilities and exceptional value.



Included Spray Patterns



High Oxygen Transfer Model

Atlantic Fountains also offers a two horsepower model in a low-profile configuration. Designed for maximum oxygen transfer this offers an option for aeration without a spray pattern.

